



DATA SHEET
MIXED METAL OXIDE
ANODE

Client:

Doc No.:

Inquiry No.:

Project:

Standard: IGS-M-TP-22

Date: 2018/14/10

1	APPLICATION TYPE	<input checked="" type="checkbox"/> Find Sand
		<input type="checkbox"/> Concrete
	TYPE OF ANODE	Ribbon
	DIMENSION & WEIGHT	Width: 6.35 mm
		Thickness: 0.635 mm
		Approx. Weight: 15 g/m
	ANODE SUBSTRATE	Titanium
	OUTPUT CURRENT	42 mA/m (3A/m ²)
LIFE TIME	25 Years	
2	CONDUCTOR BAR	Width: 12.7 mm
		Thickness: 0.9 mm
		Approx. Weight: 51 g/m
3	POWER FEED	Titanium bar : 12.7 * 0.9 * 180 mm
		Cable size: suitable for 1*16, 1*25 and 1*35 mm ²



www.bornagodaz.com Tel: 02156233929-30
info@bornagodaz.com Fax: 02156230236

Head Office: No. 2 , Golbarg 2 , Narenjestan Blvd , Shamsabad
Industrial City , Qom Old Road , Tehran , Iran

Client's Approval

Name:

Date:

Sign: