

	DATA SHEET MIXED METAL OXIDE	DOC NO.	
		TITLE:	MIXED METAL OXIDE (Tubular Type)
Standard:	NACE-TM-0108, ASTM-B 338, IGS-M-TP 22	Date:	2017/25/5

1	Anode's Shape	1.1	Tubular (String type)				
2	Dimension & Weight	2.1	Diameter: 25 mm				
		2.2	Length: 1000 mm				
		2.3	Approx. Weight: 1000 gr				
3	Anode's Quantity	3.1	6				
4	APPLICATION TYPE	4.1	Environmental Condition	Maximum Current Density(A/m ²)	OUTPUT CURRENT(A)		
			Carbon Backfill	50	4		
			Calcined petroleum Coke	100	8		
			Fresh Water	100	8		
			Saline Water	100-300	8-24		
			Sea Water	600	48		
5	LIFE TIME	5.1	25 Years				
6	Cable	6.1	Size: 1*16 mm ²				
		6.2	Length	6.2.1	Distance of Center to Center: according to request		
				6.2.2	Length of Start: according to request		
				6.2.3	Length of End: according to request		
				6.2.4	Total length: according to request		
		6.3	Cable Insulation Type	7.3.1	Standard Type	6.3.1.1	<input type="checkbox"/> Single Jacket PVC
						6.3.1.2	<input type="checkbox"/> Single Jacket HMWPE
						6.3.1.3	<input checked="" type="checkbox"/> Double Jacket XLPE /PVC
						6.3.1.4	<input type="checkbox"/> XLPE/SWA/PVC
				7.3.2	Chlorine Resistance Type	6.3.2.1	<input type="checkbox"/> Single Jacket PVDF
6.3.2.2	<input type="checkbox"/> Double Jacket PVDF/HMWPE						


 www.bornagodaz.com Tel: 02156233929-30
 info@bornagodaz.com Fax: 02156230236
 Head Office: No. 2 , Golbarg 2 , Narenjestan Blvd , Shamsabad
 Industrial City , Qom Old Road , Tehran, Iran

Client's Approval	
Name:	
Date:	
Sign:	